

Dimensions in mm

### Properties

Front door half-fitting with security escutcheon (ES1) in H-technology with roses according to DIN 18255 and EN 1906 made of stainless steel, Matt jet black, powder-coated, consisting of:

Lever handle model 271X... in L-shape made of stainless steel (1.4301), Matt jet black, powder-coated, neck diameter 21.3 mm, with stepped shoulder guide and groove, with set screw M5 as additional fixing of lever and spindle for optimal transfer of force to door leaf.

Installed by simply latching the lever handle into the base parts pre-mounted on the door. The latching can be released using the dismantling tool.

Rose 305...XAH, Rosette substructure in plastic-steel composite construction with black zinc/nickel surface for optimum corrosion protection, integrated spring-assisted restraining "hold-up" module, can be used for left or right-hand opening doors, supporting the lock for longer durability. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area to eliminate any possible installation inaccuracies. Concealed, single-sided installation with a lug disappearing into the door leaf.

Rose cap, round, made of stainless steel (1.3401), Matt jet black, powder-coated, Diameter 55 mm, 10.5 mm high, 1.5 mm wall thickness.

Security escutcheon 306.23XAESRC made of stainless steel, Matt jet black, powder-coated, external rose, solid, Diameter 55 mm, 12 mm high, hardened, in conical version, as protection against forced twisting off, Internal rose, FS type in polyamide-steel composite, Diameter 55 mm, 10.5 mm high, concealed screw connection, for mounting in pairs, Delivery with M 5 screws, holes for profiled cylinder (Euro (PZ) and KABA), for cylinder projections: 9 - 15 mm

protection class: ES 1 to DIN 18257, can be used on burglar resistant elements to EN 1627-1630

Designed and tested for projects, Category of use according to DIN EN 1906 - Class 4 Fire protection set with square spindle 8 - 8.5 - 10 mm, Class 4 fire protection set with square spindle 9 mm, acc. to DIN 18273 usage category: Class 4

Durability: Class 7

Door weight: No classification specified

fire resistance: Class B1 - fire resistance


fire resistance: Class 0 - no fire resistance:

Safety: Class 1  
Corrosion resistance: Class 4  
Burglary protection: Class 1  
Design type: A

#### **Awards**



#### **Colours / Surfaces**

 DC (matt black)