

Similar picture

Properties

Apartment fire door fitting

in R-technology with roses according to DIN 18255 and EN 1906 made of polyamide, high-polished surface, consisting of:

Knob model 138R, made of high-quality polyamide and lever handle model 114.23GKR U-shaped made of high-quality polyamide with corrosion resistant steel insert, solid colour, diameter 23 mm, with stepped shoulder guide and groove, easily installed by latching the lever handle into the base parts pre-mounted on the door. The lever handle fulfils the guidelines of the German Federal Association of Accident Insurers ("Bundesverbandes der Unfallkassen e. V." - BUK) safety margin to closing edge 25 mm.

The latching can be released using the dismantling tool. The lever handle meets the standards of EN 179 and DIN 18040.

Roses: model 315.23... and 316RFS roses substructure made of synthetic material-stainless steel composite, can be used for left and right-hand opening doors. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle. Concealed, non-loosening screwed joint.

Rose cap, oval, made of polyamide, solid colour, 31 x 72 mm, 10.5 mm high, flat, 1.5 mm wall thickness. Designed and tested for the projects segment, user category to EN 1906 - Class 4 fire door fitting with spindle 9 mm, according to DIN 18273

Telephon: +49 5691 82-0

Fax: +49 5691 82-319

user category: Class 4 Durability: Class 7

Door weight: No classification specified

Fire resistance: Class D1

Safety: Class 1

Corrosion resistance: Class 5 Burglary protection: Class 0

Design-type: U

Sustainability: EPD Environmental Product Declaration


Awards





Colours / Surfaces

	99 (pure white)
ú.	98 (signal white)
	97 (light grey)
2	95 (stone grey)



18 (mustard yellow)

Telephon: +49 5691 82-0

Fax: +49 5691 82-319