

Dimensions in mm

Similar picture

Properties



Lever handle for glass door locks

in R-technology with roses according to DIN 18255 and EN 1906 made of polyamide, Edition matt surface, consisting of:

Lever handle 162.21P... in mitre cut, made of high-quality polyamide with corrosion resistant steel insert, solid colour, diameter 21.3 mm, with stepped shoulder guide and groove, easily installed by latching the lever handle into the base parts pre-mounted on the door. The latching can be released using the dismantling tool. Fits Dorma Junior Office and Schlechtendahl Atelier F / R and Studio - Private Line. The locks are prepared for rose fixing. Roses 305.21R substructure made of synthetic material-stainless steel composite, can be used for left and right-hand opening doors. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle. Concealed, non-loosening screwed joint with M4 screw and sleeve combination as well as the pivot disappearing into the lock.

Rose cap, round, made of high-quality polyamide, solid colour, diameter 55 mm, 10 mm high, 1.5 mm wall thickness.

Colours / Surfaces

- | | |
|---|-----------------|
|  | 99 (pure white) |
|  | 90 (jet black) |