



Properties

Vacant/occupied fitting Barbie™ x HEWI

- Official Barbie™ licensed product
- made of high-gloss polyamide in HEWI colour 47 (pink)
- incl. Barbie™ logo
- in R technology for door thickness 28 to 38 mm with roses to DIN 18255 and DIN EN 1906
- Set with square spindle 8 mm
- U-shaped lever handle made of polyamide with continuous steel core up to the lever handle end, through-dyed, Diameter 23 mm, with stepped shoulder guide and groove, Installation by simply snapping the lever handles into the pre-mounted bases on the door. The latching can be released using the dismantling tool.
- The lever handle fulfils the requirements of DIN EN 179 and DIN 18040.
- Rosette substructure in plastic-stainless steel composite construction, can be used DIN left and DIN right. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle.
- Concealed, Loosening-proof screw connection with M4 screw and sleeve screw combination as well as support plugs recessed into the door leaf.
- WC version with coin-operated emergency opening and indicator disc (red/white indicator) on the outside.
- Rosette cover cap, round, Made of polyamide, coloured throughout, Diameter 55 mm, 10.5 mm high, flat, 1.5 mm wall thickness.
- Designed and tested for the contract sector, Utilisation category according to DIN EN 1906 - Class 4
- Durability: Class 7
- Door dimensions: no classification specified
- Fire resistance: Class 0
- Security: Class 1
- Corrosion resistance: Class 5
- Burglary protection: Class 0
- Execution type: U
- Sustainability: EPD Environmental Product Declaration

Awards



Certificates

