



Dimensions in mm

Properties

hinged support rail Duo, Design (B), System 900

- Two parallel rails, round gripping levels arranged on top of each other
- with toilet roll holder and flush release (electric version)
- Version right
- Can be folded upwards and folded downwards with braked movement
- Blue button (wave symbol) is used to activate the toilet flush
- Cable with free cable ends for wall connection
- Includes white cover for flush-mounted box
- Control voltage max. 30 V = SELV, PELV, switching current up to max. 2 A
- Suitable for all standard concealed cisterns with electrical control
- Projection 850 mm , Height 256 mm and width 75 mm , diameter of upper rail 33.7 mm, diameter of bottom rail 25 mm
- Made from high-quality stainless steel, matt polished
- Wall plate made of polyamide with integrated steel core and cover made of matt polished stainless steel
- for mounting with non-corrosive and tested HEWI fixing material for different wall systems (to be ordered separately).

Sealing tape for sealing the fixing points is included in the delivery

- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- Floor supports 900.50.020XA and 900.50.021XA can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices
- Fulfils the DIN 18040 requirements, ÖNORM B1600/1601 and SIA 500

Awards



Certificates

