





Similar picture Dimensions in mm

Properties

hinged support rail Duo, Design (A), System 900

- · Two parallel rails, round gripping levels arranged on top of each other
- · with radio flush release
- · left-hand version
- · Can be folded upwards and folded downwards with braked movement
- Blue button (wave symbol) is used to activate the toilet flush
- Transmission frequency 868.4 MHz
- Suitable for wireless WC flushing systems from Geberit, Mepa, Viega, Sanit, Friatec, TECE and Grohe
- Projection 850 mm, Height 210 mm and width 101 mm, diameter of upper rail 33.7 mm, diameter of bottom rail 25 mm
- · Made from high-quality stainless steel, chrome-plated
- for mounting with non-corrosive and tested HEWI fixing material for different wall systems (to be ordered separately).

Sealing tape for sealing the fixing points is included in the delivery

- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- Floor supports 900.50.02040 and 900.50.02140 can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices

Telephon: +49 5691 82-0

Fax: +49 5691 82-319

Fulfils the DIN 18040 requirements, ÖNORM B1600/1601 and SIA 500

Awards













Certificates



info@hewi.de

www.hewi.com