





Dimensions in mm

Properties

hinged support rail Duo, Design (B), System 900

- · Two parallel rails, round gripping levels arranged on top of each other
- with radio flush release
- · left-hand version
- · Can be folded upwards and folded downwards with braked movement
- Blue button (wave symbol) is used to activate the toilet flush
- Transmission frequency 868.4 MHz
- Suitable for wireless WC flushing systems from Geberit, Mepa, Viega, Sanit, Friatec, TECE and Grohe
- Projection 750 mm, Height 256 mm and width 75 mm, diameter of upper rail 33.7 mm, diameter of bottom rail 25 mm
- Made from high-quality stainless steel, powder-coated in HEWI colours DX (deep matt white), DC (matt black) and SC (matt dark grey pearl mica)
- Wall plate made of polyamide with integrated steel core and stainless steel cover, powder-coated in HEWI colours DX (deep matt white), DC (matt black) and SC (matt dark grey pearl mica)
- for mounting with non-corrosive and tested HÉWI fixing material for different wall systems (to be ordered separately).

Sealing tape for sealing the fixing points is included in the delivery

- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- Floor supports 900.50.02060 and 900.50.02160 can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices

Telephon: +49 5691 82-0

Fax: +49 5691 82-319

 fulfils the requirements applicable in Belgium (CWATUPE, WVG Vlaanderen) with regard to the projection of the folding support handle on the WC

Awards











Certificates





Colours / Surfaces

SC (matt dark grey pearl mica)
DX (matt white)
DC (matt black)

Telephon: +49 5691 82-0

Fax: +49 5691 82-319