



Dimensions in mm

### Properties

Hinged support rail, rotatable, from the 805 Classic range

- with integrated flush release, model E
- Two parallel rails, arranged on top of each other, and joined together by a connecting arch (formed from a continuous tube)
- Used for holding and supporting - Wall plate made of polyamide with integrated steel core
- Can be folded upwards and, folded downwards with braking mechanism, in raised position can be turned to left or right towards the wall
- blue button for triggering the WC flush mechanism
- spiral cable with bare wire ends for wall connection
- Includes white cover for flush-mounted box
- Control voltage max. 30 V = SELV, PELV, switching current up to max. 2 A
- Suitable for all standard concealed cisterns with electrical control
- Mounting on the wall with wall-specific HEWI mounting material (to be ordered separately)

Sealing tape for sealing the fixing points is included in the delivery

- Concealed mounting
- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- Projection 700 mm , Height 259 mm and width 78 mm , Rail 33 mm in diameter, pipe thickness 2 mm
- made of high-quality stainless steel, matt satin surface
- Toilet roll holder 805.50.015 and floor supports 950.50.022XA and 950.50.024XA retrofittable
- Produced in accordance with Regulation (EU) 2017/745 on medical devices
- Fulfils the ÖNORM B1600/1601 and SIA 500 requirements

### Certificates

