

Dimensions in mm

### Properties


Grab rail with additional support positioned in the centre, System 900



- Straight bar with uprights and rosettes moulded to the wall
- Centre distance 48 1/16 inch (1220 mm), 2 3/4 inch (70 mm) deep
- rail diameter 1 1/4 inch (32 mm), tube thickness 1/16 inch (2 mm), rose diameter 2 3/4 inch (70 mm)
- weight capacity up to 330 lbs (150 kg)
- made of high-quality stainless steel, PVD coated
- including corrosion-free and tested HEWI fixing material for wall mounting and sealing tape to seal the drilling points
- fulfils the requirements according to 2010 ADA Standards and ICC/ANSI A117.1-2017


### Awards



### Colours / Surfaces

|                                                                                     |                     |
|-------------------------------------------------------------------------------------|---------------------|
|  | WR (brushed nickel) |
|  | VT (brushed gold)   |
|  | UN (bronze glossy)  |
|  | SV (brushed bronze) |

|                                                                                     |                     |
|-------------------------------------------------------------------------------------|---------------------|
|  | RB (brushed copper) |
|  | LP (brushed brass)  |
|  | JL (shiny nickel)   |
|  | DP (shiny copper)   |

|                                                                                       |                  |
|---------------------------------------------------------------------------------------|------------------|
|  | CK (shiny brass) |
|  | BZ (shiny gold)  |