



Dimensions in mm

Properties

hinged support rail Duo, Design (A), System 900

- Two parallel rails, round gripping levels arranged on top of each other
- with toilet roll holder and radio flush release
- left-hand version
- Can be folded upwards and folded downwards with braked movement
- Blue button (wave symbol) is used to activate the toilet flush
- Transmission frequency 868.4 MHz
- Suitable for wireless WC flushing systems from Geberit, Mepa, Viega, Sanit, Friatec, TECE and Grohe
- Projection 900 mm , Height 210 mm and width 101 mm , diameter of upper rail 33.7 mm, diameter of bottom rail 25 mm
- Made from high-quality stainless steel, PVD coated
- for mounting with non-corrosive and tested HEWI fixing material for different wall systems (to be ordered separately).

Sealing tape for sealing the fixing points is included in the delivery

- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- Floor supports 900.50.02070 and 900.50.02170 can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices
- fulfils the requirements of ÖNORM B1600/1601

Awards



Certificates



Colours / Surfaces

| | | |
|---|---|--|
|  WR (brushed nickel) |  RB (brushed copper) |  CK (shiny brass) |
|  VT (brushed gold) |  LP (brushed brass) |  BZ (shiny gold) |
|  UN (bronze glossy) |  JL (shiny nickel) | |
|  SV (brushed bronze) |  DP (shiny copper) | |