



Similar picture

Dimensions in mm

Properties

Folding support rail Duo System WARM TOUCH

- with two handle levels arranged one above the other
- Lower rail is guided at an angle of 135° to the upper rail
- Upper rail (diameter 33 mm) is used for holding and supporting
- Lower rail (diameter 25 mm) is positioned at a distance of 250 mm from the front edge of the upper rail and is used to hold it in place and turn it in sideways
- Projection 850 mm, wall-mounting plate cover 181 mm high and 130 mm wide
- Can be folded upwards and folded downwards with braked movement
- Made from high-quality chrome-optic coated polyamide with a warm feel
- With continuous, Corrosion-protected steel core and integrated steel wall plate with cover made of chrome-optic coated polyamide
- Stable three-point attachment
- for wall mounting with concealed, Corrosion-free and tested fastening material for different wall structures (to be ordered separately)

Sealing tape for sealing the fixing points is included in the delivery

- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- with toilet roll holder 950.50.01050, Toilet roll holder with toilet flush release 950.50.07090 (right), 950.50.07190 (left), and floor supports 950.50.020XA, 950.50.025XA and 950.50.026XA can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices
- Fulfils the DIN 18040 requirements, ÖNORM B1600/1601 and SIA 500

Awards



Certificates

