



Properties

Mobile hinged seat, System 900

- Construction consisting of wall console and continuous seat surface
- anti-slip, Structured seat made of white plastic
- Aluminium seat reinforcement, powder coated in the colour of the seat
- Wall bracket made of high-quality stainless steel, PVD coated
- Seat with hygiene cut-out can be folded up to save space
- Seat depth when folded up 77 mm
- for mobile use
- for easy and flexible retrofitting on existing, pre-assembled mounting plate: 900.51.00170 (to be ordered separately)
- Quick and tool-free installation by simply attaching the seat
- Secured with fixing screw
- 450 mm wide, 528 mm deep and 112 mm high
- Seat 450 mm wide and 450 mm deep
- for mounting with non-corrosive and tested HEWI fixing material for different wall systems (to be ordered separately).
- Sealing tape and sealing rods for sealing the mounting points according to DIN 18534 are included in the delivery
- tested up to 200 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- Fulfils the DIN 18040 requirements, ÖNORM B1600/1601 and SIA 500

Awards



Colours / Surfaces

	WR (brushed nickel)		RB (brushed copper)		CK (shiny brass)
	VT (brushed gold)		LP (brushed brass)		BZ (shiny gold)
	UN (bronze glossy)		JL (shiny nickel)		
	SV (brushed bronze)		DP (shiny copper)		