

Dimensions in mm

Properties

Apartment door fitting

in H-technology with roses according to DIN 18255 and EN 1906 made of stainless steel, PVD coated, consisting of:

Knob model 276X in stainless steel and lever handle Model 271X... with L-shape in stainless steel (1.4301), PVD coated, Lug diameter 21.3 mm, with stepped shoulder guide and groove, with M5 grub screw as additional fixing of lever and spindle for optimal transfer of force to door leaf.

Installed by simply latching the lever handle into the base parts pre-mounted on the door. The latching can be released using the dismantling tool.

Rosette substructure in Synthetic material/steel composite construction with black zinc/nickel surface for optimum anti-corrosion protection, integrated spring-assisted restraining "hold-up" module, can be used for left or right-hand opening doors, supporting the lock for longer durability. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area to eliminate any possible installation inaccuracies. Concealed, Loosening-proof screw connection with M5 stainless steel screw and sleeve screw combination as well as tenons recessed into the door leaf.

Rose cap, round, made of stainless steel (1.3401), Diameter 55 mm, 10.5 mm high, 1.5 mm wall thickness. PVD coated

Designed and tested for projects, Category of use according to DIN EN 1906 - Class 4 Fire protection set with square spindle 8- 8.5 mm

usage category: Class 4

Durability: Class 7

Door weight: No classification specified

fire resistance: Class 0

Safety: Class 1

Corrosion resistance: Class 4

Burglary protection: Class 0

Design type: A





Awards




Certificates



Colours / Surfaces

	WR (brushed nickel)
	VT (brushed gold)
	SV (brushed bronze)
	RB (brushed copper)

	LP (brushed brass)
---	--------------------