



Dimensions in mm

### Properties

#### Hinged support rail Duo System 800 K

- with two handle levels arranged one above the other
- Lower rail is guided at an angle of 135° to the upper rail
- Upper rail (diameter 33 mm) is used for holding and supporting
- Lower rail (diameter 25 mm) is positioned at a distance of 250 mm from the front edge of the upper rail and is used to hold it in place and turn it in sideways
- Projection 700 mm , wall-mounting plate cover 181 mm high and 130 mm wide
- Can be folded upwards and folded downwards with braked movement
- Folding support handle made of high-quality polyamide in HEWI colour 98 (signal white)
- Upper rail according to HEWI colour chart
- With continuous, corrosion resistant steel core and integrated wall mounting plate made of steel with high-quality polyamide cover
- Stable three-point attachment
- for wall mounting with concealed, Corrosion-free and tested fastening material for different wall structures (to be ordered separately)

Sealing tape for sealing the fixing points is included in the delivery

- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- with toilet roll holder 950.50.01090, Toilet roll holder with toilet flush release 950.50.07090 (right), 950.50.07190 (left) and floor supports 950.50.020XA, 950.50.025XA and 950.50.026XA can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices
- Fulfils the ÖNORM B1600/1601 and SIA 500 requirements

### Certificates



### Colours / Surfaces

- 92 (anthracite grey)
- 33 (ruby red)