Dimensions in mm





Similar picture

## **Properties**

hinged support rail Duo

- with two handle levels arranged one above the other
- Lower rail is guided at an angle of 135° to the upper rail
- Top rail made of square profile, 40 mm wide and 30 mm high, offers a wide support surface and large radii for comfortable gripping, Used for holding and supporting
- Lower rail (diameter 25 mm) is positioned at a distance of 250 mm from the front edge of the upper rail and is used to hold it in place and turn it in sideways
- · Projection 850 mm , wall-mounting plate cover 181 mm high and 130 mm wide
- Can be folded upwards and folded downwards with braked movement
- made of metal, high-quality chrome-plated
- · High-quality chrome-plated plastic wall plate cover
- Stable three-point attachment
- for wall mounting with concealed, Corrosion-free and tested fastening material for different wall structures (to be ordered separately)

Sealing tape for sealing the fixing points is included in the delivery

- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- with toilet roll holder 950.50.01150, Toilet roll holder with toilet flush release 950.50.07290 (right), 950.50.07390 (left), Floor supports 950.50.020XA, 950.50.025XA, 950.50.026XA and arm pad 950.50.03192 can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices
- Fulfils the DIN 18040 requirements, ÖNORM B1600/1601 and SIA 500

Certificates

CE

Technical information subject to alteration, 02.02.2025