



Similar picture

Dimensions in mm

### Properties

Mobile hinged support rail Duo System 800 K

- for easy and flexible retrofitting on existing, pre-assembled mounting plate: 950.50.014XA, must be ordered separately
- for mobile use
- with two handle levels arranged one above the other
- Lower rail is guided at an angle of 135° to the upper rail
- Upper rail (diameter 33 mm) is used for holding and supporting
- Lower rail (diameter 25 mm) is positioned at a distance of 250 mm from the front edge of the upper rail and is used to hold it in place and turn it in sideways
- Projection 700 mm, bracket 181 mm high and 130 mm wide
- Can be folded upwards and folded downwards with braked movement
- made of high-quality polyamide in the HEWI colours 98 (signal white) or 99 (pure white)
- With continuous, with continuous, anti-corrosion steel core and bracket made of steel with cover made of high-quality polyamide
- Quick and tool-free installation thanks to simple, Short suspension
- Secured against unintentional removal
- Unlocking for flexible use by means of spring actuation
- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- with toilet roll holder 950.50.01090, Toilet roll holder with toilet flush release 950.50.07090 (right), 950.50.07190 (left) and floor supports 950.50.020XA, 950.50.025XA and 950.50.026XA can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices
- Fulfils the ÖNORM B1600/1601 and SIA 500 requirements

### Certificates



### Colours / Surfaces

- |  |                   |
|--|-------------------|
|  | 99 (pure white)   |
|  | 98 (signal white) |