

Dimensions in mm

### Properties



Mobile hinged support rail Duo System 800 K

- for easy and flexible retrofitting on existing, pre-assembled mounting plate: 950.50.014XA, must be ordered separately
- for mobile use
- with two handle levels arranged one above the other
- Lower rail is guided at an angle of 135° to the upper rail
- Upper rail (diameter 33 mm) is used for holding and supporting
- Lower rail (diameter 25 mm) is positioned at a distance of 250 mm from the front edge of the upper rail and is used to hold it in place and turn it in sideways
- Projection 850 mm, bracket 181 mm high and 130 mm wide
- Can be folded upwards and folded downwards with braked movement
- Folding support handle made of high-quality polyamide in HEWI colour 99 (pure white)
- Top rail made of high-quality polyamide according to HEWI colour chart
- With continuous, with continuous, anti-corrosion steel core and bracket made of steel with cover made of high-quality polyamide
- Stable three-point attachment
- Quick and tool-free installation thanks to simple, Short suspension
- Unlocking for flexible use by means of spring actuation
- tested up to 150 kg when used with HEWI fixing material
- Recommended maximum weight of the user: 150 kg
- with toilet roll holder 950.50.01090, Toilet roll holder with toilet flush release 950.50.07090 (right), 950.50.07190 (left) and floor supports 950.50.020XA, 950.50.025XA and 950.50.026XA can be retrofitted
- is produced in accordance with CE and UKCA Regulation (EU) 2017/745 on medical devices
- Fulfils the DIN 18040 requirements, ÖNORM B1600/1601 and SIA 500

### Certificates



### Colours / Surfaces

-  92 (anthracite grey)
-  33 (ruby red)