
















<b>Serie 805 Classic</b> <b>Kompatibilität Einhängesitze und Stangen</b>  Range 805 Classic Compatibility Removable hanging seat and rails												
			900.51.10060 900.51.10660	900.51.10260 900.51.10460 900.51.10860 900.51.11060 900.51.11260	900.51.10160 900.51.10760	900.51.10360 900.51.10560 900.51.10960 900.51.11160 900.51.11360	950.51.11090 950.51.11190	950.10090 950.10190	801.51.100 801.51B100 801.51D100 801.51FR101 801.51BFR101 801.51.106 801.51.107	801.51.110 801.51B110 801.51D110 801.51CH110 801.51BCH110 801.51DCH110 801.51.115 801.51B115 801.51D115 801.51.116 801.51.117	802.51.13160 802.51.13360 802.51.13560 802.51.13760 802.51.13960 802.51.14160 802.51.14360 802.51.14560	802.51.13260 802.51.13460 802.51.13660 802.51.13860 802.51.14060 802.51.14260 802.51.14460 802.51.14660
	805.36.100	A1=300 mm	—	—	—	—	—	—	—	—	—	—
	805.36.110	A1=400 mm	✓	✓	✓	✓	✓	✓	—	—	—	—
	805.36.120	A1=500 mm	✓	✓	✓	✓	✓	✓	✓	—	✓	✓
	805.36.130	A1=600 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.36.140	A1=900 mm	—	—	—	—	—	—	—	—	—	—
	805.36.150	A1=1100 mm	—	—	—	—	—	—	—	—	—	—
	805.36.1S	A1=220-850 mm ohne zusätzliche Stütze without additional support A1=851-1300 mm zusätzliche Stütze mittig additional support in the centre	A1 min. 348	A1 min. 348	A1 min. 348	A1 min. 348	A1 min. 420 mm	A1 min. 420 mm	A1 min. 479 mm	A1 min. 582 mm	A1 min. 438 mm	A1 min. 438
	805.33.210R 805.33.210L	W1=600 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.33.220R 805.33.220L	W1=600 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.33.2S	W1=300-850 mm	W1 min. 348 mm	W1 min. 348 mm	W1 min. 348 mm	W1 min. 348 mm	W1 min. 420 mm	W1 min. 420 mm	W1 min. 479 mm	W1 min. 582 mm	W1 min. 438 mm	W1 min. 438 mm
	805.35.110	W1=762 mm W2=762 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.1S	W1/W2=475-1039 mm ohne zusätzliche Stütze without additional support	W1 min. 505 mm W2 min. 505 mm	W1 min. 505 mm W2 min. 505 mm	W1 min. 613 mm W2 min. 613 mm	W1 min. 613 mm W2 min. 613 mm	W1 min. 577 mm W2 min. 577 mm	W1 min. 577 mm W2 min. 577 mm	W1 min. 636 mm W2 min. 636 mm	W1 min. 739 mm W2 min. 739 mm	W1 min. 595 mm W2 min. 595 mm	W1 min. 686 mm W2 min. 686 mm
		W1/W2=1040-1199 mm Stützenabstand 850 mm Support spacing 850 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	W1/W2=1200-1800 mm zusätzliche Stütze mittig additional support in the centre	✓	✓	✓	✓	✓	✓	✓	W1 min. 1289 mm W2 min. 1289 mm	✓	✓	
	805.35.210R 805.35.210L	W1=762 mm W2=762 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.220R 805.35.220L	W1=762 mm W2=762 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.230R 805.35.230L	W1=762 mm W2=962 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.240R 805.35.240L	W1=762 mm W2=962 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.21S	W1/W2=475-1039 mm ohne zusätzliche Stütze without additional support W1/W2=1040-1199 mm Stützenabstand 850 mm Support spacing 850 mm W1/W2=1200-1800 mm zusätzliche Stütze mittig additional support in the middle	W1 min. 505 mm W2 min. 505 mm	W1 min. 505 mm W2 min. 505 mm	W1 min. 613 mm W2 min. 613 mm	W1 min. 613 mm W2 min. 613 mm	W1 min. 577 mm W2 min. 577 mm	W1 min. 577 mm W2 min. 577 mm	W1 min. 636 mm W2 min. 636 mm	W1 min. 739 mm W2 min. 739 mm	W1 min. 595 mm W2 min. 595 mm	W1 min. 686 mm W2 min. 686 mm
	W1/W2=1200-1800 mm zusätzliche Stütze mittig additional support in the middle	✓	✓	✓	✓	✓	✓	✓	W1 min. 1289 mm W2 min. 1289 mm	✓	✓	
	805.35.300	W1=1185 mm W2=762 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.320	W1=1185 mm W2=762 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.310	W1=762 mm W2=762 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.330	W1=762 mm W2=762 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.340	W1=962 mm W2=962 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	805.35.350	W1=962 mm W2=962 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
805.35.3S	W1/W2=475-1039 mm ohne zusätzliche Stütze without additional support	W1 min. 565 mm W2 min. 505 mm	W1 min. 565 mm W2 min. 505 mm	W1 min. 673 mm W2 min. 613 mm	W1 min. 673 mm W2 min. 613 mm	W1 min. 637 mm W2 min. 577 mm	W1 min. 637 mm W2 min. 577 mm	W1 min. 696 mm W2 min. 636 mm	W1 min. 799 mm W2 min. 739 mm	W1 min. 655 mm W2 min. 595 mm	W1 min. 746 mm W2 min. 686 mm	
	W1/W2=1040-1199 mm Stützenabstand 850 mm Support spacing 850 mm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	W1/W2=1200-1800 mm W2 zusätzliche Stütze mittig W2 additional support in the centre	✓	✓	✓	✓	✓	✓	✓	W1 min. 1349 mm W2 min. 1289 mm	✓	✓	