

Properties

Standard door fitting

in T-technology with stainless steel rosettes to DIN 18255 and DIN EN 1906, Matt jet black, powder-coated, consisting of:

Lever handle model 111X... made of stainless steel round tube (1.4301), Diameter 21.3 mm with 1.5 mm wall thickness, with attachment guide and M5 grub screw to fix the lever handle to the square spindle.

The lever handle fulfils the requirements of DIN 18040.

Quick installation of the lever handles in the base parts pre-assembled on the door. Loosening-proof connection between pin and lever handle.

Plastic rose bases with support plugs recessed into the door leaf. Concealed, Loosening-proof screw connection.

Rose cap, round, made of stainless steel (1.3401), Diameter 55 mm, 10.5 mm high, 1.5 mm wall thickness.

Surface matt jet black powder-coated

Designed and tested for solid leaf doors in medium-frequented commercial buildings, Utilisation category according to DIN EN 1906 - class 4 (square 8 or 8.5 mm). Set with square spindle 7, 8 or 8.5 mm for door thicknesses from 28.1 - 58.0 mm.

Utilisation category: Class 4

Durability: Class 7

Door weight: No classification specified

fire resistance: Class 0

Safety: Class 1

Corrosion resistance: Class 4

Burglary protection: Class 0

Design type: U


Awards



Certificates



Colours / Surfaces

 DC (matt black)