

### Properties

Lever handle for glass door locks















in R-technology with roses according to DIN 18255 and EN 1906 made of polyamide, high-polished surface, consisting of:

Lever handle 111.23R U-shaped made of high-quality polyamide with corrosion resistant steel insert, solid colour, diameter 23 mm, with stepped shoulder guide and groove, easily installed by latching the lever handle into the base parts pre-mounted on the door. The latching can be released using the dismantling tool. Fits Dorma Junior Office and Schlechtendahl Atelier F / R and Studio - Private Line. The locks are prepared for rose fixing. The lever handle meets the standards of EN 179 and DIN 18040.

Roses: model 305.23R substructure made of synthetic material-stainless steel composite, can be used for left and right-hand opening doors. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle. Concealed, non-loosening screwed joint with M4 screw and sleeve combination as well as the pivot disappearing into the lock.

Rose cap, round, made of high-quality polyamide, solid colour, diameter 55 mm, 10 mm high, 1.5 mm wall thickness.

### Colours / Surfaces

|   |  |  |  |
|---|--|--|--|
|  18 (mustard yellow) |  55 (aqua blue) |  92 (anthracite grey) |  99 (pure white)  |
|  33 (ruby red)       |  84 (umber)     |  95 (stone grey)      |  74 (apple green) |
|  36 (coral)          |  86 (sand)      |  97 (light grey)      |  |
|  50 (steel blue)     |  90 (jet black) |  98 (signal white)    |  |