







Similar picture

## **Properties**

Vacant/Engaged fitting

Flat roses according to DIN 18255 and EN 1906 and inlay made of solid coloured high-quality matt polyamide, consisting of:

Lever handle design 111.23PB... in U-shape made of solid coloured high-quality matt polyamide, with continuous steel core up to the end of the lever handle, through-dyed, 23 mm diameter, with stepped shoulder guide and latching groove, with grubscrew M5, for additional fixing of the door lever handle on the square spindle, for optimal transfer of force to door leaf. the lever handle meets the standards of DIN 18040.

Flat lever rose and rose with turn knob 306.23PBVI..., round, diameter 52 mm, 4.0 mm high. Concealed, non-loosening connection: Fixed rotating bearing of the lever handle and the roses, and in the door leaf dipping support pin. Easy and fast assembly, by snapping in pre-assembled assemblies. Toilet version with emergency opening by means of coin and optionally with or without occupancy disc (red/green indicator) on the outside. Rose material made of stainless steel (1.4301) matt in PVD-coating.

Rose inserts made of solid coloured high-quality matt polyamide

Designed and tested for the projects segment, user category to EN 1906 - Class 4

Telephon: +49 5691 82-0

Fax: +49 5691 82-319

Durability: Class 7

Door weight: No classification specified

Fire resistance: Class 0

Safety: Class 1

Corrosion resistance: Class 4 Burglary protection: Class 0 Type of operation: U

## **Awards**







## Colours / Surfaces

99 (pure white)
92 (anthracite grey)
90 (jet black)