Zestaw klamek pokojowych HEWI
111PBR01.130





Wymiary w mm

Właściwości
Standard door fitting
in R-technology with roses according to DIN 18255 and EN 1906 made of solid coloured high-quality matt polyamide, consisting of:
Lever handle model 111PBR U-shaped made of matt polyamide with corrosion resistant steel insert, diameter 20 mm, with stepped shoulder guide and groove, easily installed by latching the lever handle into the base parts pre-mounted on the door.
The latching can be released using the dismantling tool. The lever handle meets the standards of EN 179 and DIN 18040.
Roses: model 305.20PB... and 306.23PB roses substructure made of synthetic material-stainless steel composite, can be used for left and right-hand opening doors. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle. Concealed, non-loosening screwed joint with M4 screw and sleeve combination as well as the pivot disappearing into the door leaf.
Rose cap, round, made of solid coloured high-quality matt polyamide, diameter 55 mm, 10.5 mm high, flat, 1.5 mm wall thickness.
Designed and tested for the projects segment, user category to EN 1906 - Class 4 fitting with spindle 8 - 8.5 mm
user category: Class 4
Durability: Class 7
Door weight: No classification specified
Fire resistance: Class 0
Safety: Class 1
Corrosion resistance: Class 5
Burglary protection: Class 0
Design-type: U
Sustainability: EPD Environmental Product Declaration

Wyróżnienia

Certyfikaty

Kolory / Powierzchnie

- 99 (czysta biel)
- 98 (sygnał biały)
- 97 (jasnoszary)
- 95 (szary kamień)
- 92 (szary antracytowy)
- 90 (czerń jetowa)

HEWI Heinrich Wilke GmbH
Sp. z o.o. Oddz. w Polsce
Ul. Lelka 26
02-812 Warszawa
Tel.: 22 330 00 51
Faks: 22 330 00 50
info@hewi.pl