

Podobne zdjęcie

Właściwości

Standard door fitting without escutcheons

Flat roses according to DIN 18255 and EN 1906 and inlay made of polyamide, consisting of:

Lever handle design 111.23P... in U-shape made of polyamide, with continuous steel core up to the end of the lever handle, through-dyed, 23 mm diameter, with stepped shoulder guide and latching groove, with grubscrew M5, for additional fixing of the door lever handle on the square spindle, for optimal transfer of force to door leaf. the lever handle meets the standards of DIN 18040.

Flat lever roses, 305..., round, diameter 52 mm, 4.0 mm high. Concealed, non-loosening connection: Fixed rotating bearing of the lever handle and the roses, and in the door leaf dipping support pin. Easy and fast assembly, through preassembled assemblies.

Rose material made of stainless steel (1.4301) in PVD-coating, rose inserts made of polyamide high-gloss
Designed and tested for the projects segment, user category to EN 1906 - Class 4

Durability: Class 7

Door weight: No classification specified

Fire resistance: Class 0

Safety: Class 1

Corrosion resistance: Class 4




Burglary protection: Class 0

Design-type: U

Wyróżnienia



Kolory / Powierzchnie

	90 (czerń jetowa)
	92 (szary antracytowy)
	99 (czysta biel)