



Similar picture

### Properties

Standard door fitting

in R-technology with roses according to DIN 18255 and EN 1906 made of polyamide, high-polished surface, consisting of:

Lever handle model 111R U-shaped made of high-quality polyamide with corrosion resistant steel insert, solid colour, diameter 20 mm, with stepped shoulder guide and groove, easily installed by latching the lever handle into the base parts pre-mounted on the door.

The latching can be released using the dismantling tool. The lever handle meets the standards of EN 179 and DIN 18040.

Roses: model 305.20... and 306.23 roses substructure made of synthetic material-stainless steel composite, can be used for left and right-hand opening doors. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle. Concealed, non-loosening screwed joint with M4 screw and sleeve combination as well as the pivot disappearing into the door leaf.

Rose cap, round, made of high-quality polyamide, solid colour, diameter 55 mm, 10.5 mm high, flat, 1.5 mm wall thickness.

Designed and tested for the projects segment, user category to EN 1906 - Class 4 fitting with spindle 8 - 8.5 mm user category: Class 4

Durability: Class 7

Door weight: No classification specified

Fire resistance: Class 0

Safety: Class 1

Corrosion resistance: Class 5

Burglary protection: Class 0

Design-type: U

### Awards



### Certificates



### Colours / Surfaces

|   |   |  |   |
|---|---|--|---|
|  18 (mustard yellow) |  50 (steel blue) |  86 (sand)            |  97 (light grey)   |
|  24 (orange)         |  55 (aqua blue)  |  90 (jet black)       |  98 (signal white) |
|  33 (ruby red)       |  72 (may green)  |  92 (anthracite grey) |  99 (pure white)   |
|  36 (coral)          |  84 (umber)      |  95 (stone grey)      |  74 (apple green)  |

Technical information subject to alteration, 02.01.2024