

Dimensions in mm

Properties

Fire door fitting for framed doors
in R-technology with roses according to DIN 18255 and EN 1906 made of polyamide, high-polished surface, consisting of:
Lever handle model 111.23R U-shaped made of high-quality polyamide with corrosion resistant steel insert, solid colour, diameter 23 mm, with stepped shoulder guide and groove, easily installed by latching the lever handle into the base parts pre-mounted on the door.
The latching can be released using the dismantling tool. The lever handle meets the standards of EN 179 and DIN 18040.
Rose: model 315.23R, rose substructure made of synthetic material-stainless steel composite, can be used for left and right-hand opening doors. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle. Concealed, non-loosening screwed joint.
Rose cap, oval, made of polyamide, solid colour, 32 x 72 mm, 12 mm high, flat, 1.5 mm wall thickness.
Designed and tested for the projects segment, user category to EN 1906 - Class 4 fire door fitting with spindle 9 mm, according to DIN 18273
user category: Class 4
Durability: Class 7
Door weight: No classification specified
Fire resistance: Class D1
Safety: Class 1
Corrosion resistance: Class 5
Burglary protection: Class 0
Design-type: U
Sustainability: EPD Environmental Product Declaration

Awards

Certificates

Colours / Surfaces

24 (orange)	55 (aqua blue)	86 (sand)	97 (light grey)
33 (ruby red)	72 (may green)	90 (jet black)	98 (signal white)
36 (coral)	74 (apple green)	92 (anthracite grey)	99 (pure white)
50 (steel blue)	18 (mustard yellow)	95 (stone grey)	84 (umber)

HEWI Heinrich Wilke GmbH
Postfach 1260
D-34442 Bad Arolsen

Telephon: +49 5691 82-0
Fax: +49 5691 82-319

info@hewi.de
www.hewi.com