



Dimensions in mm

Properties

Counter fitting for panic bar 162XA...

in H-technology with signs according to DIN 18255 and EN 1906 made of stainless steel, deep matt black powder-coated, consisting of:

Lever handle 162X... made of stainless steel tube in mitre cut (1.4301), black deep matt powder-coated, diameter 21.3 mm with 1.5 mm wall thickness, with stepped shoulder guide and groove, with set screw M5 as additional fixing of lever and spindle, for optimal transfer of force to door leaf.

Installed by simply latching the lever handle into the base parts preassembled on the door. The latching can be released using the dismantling tool.

Backplate 219.21X... Composite synthetic material and steel backplate substructure with black zinc/nickel surface for optimum corrosion protection, fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle. Concealed, non-loosening screwed joint with M5 stainless steel screws sleeve-screw combination as well as the pivot disappearing into the door leaf, additional blind plate for paired mounting with the panic bar on the hinge side

Escutcheon cover cap made of stainless steel (1.4301), deep matt black powder coated, 33 x 203 mm, 10.5 mm high, 1.5 mm wall thickness.

Designed and tested for the projects segment, user category to EN 1906 - Class 4 fire door fitting with spindle 9 mm, according to DIN 18273

Category of use: Class 4

Durability: Grade 7

Door weight: No classification specified

Fire resistance: Class B1

Safety: Grade 1

Corrosion resistance: Class 4

Security: Grade 0

Type of operation: U

Colours / Surfaces

■ DC (matt black)