

Dimensions in mm

Properties
Standard door fitting
in H-technology with roses according to DIN 18255 and EN 1906 made of stainless steel, consisting of:
Lever handle 173X... made of stainless steel (1.4301), solid, diameter 21.3 mm, length 141.9 mm mm, with stepped shoulder guide and groove, with set screw M5 as additional fixing of lever and spindle, for optimal transfer of force to door leaf. the lever handle meets the standards of EN 179.
Installed by simply latching the lever handle into the base parts preassembled on the door. The latching can be released using the dismantling tool.
Roses: model 305.21X... and 306.23X..., 305.21X... composite synthetic material and steel rose substructure with black zinc/nickel surface for optimum corrosion protection, integrated spring-assisted restraining "hold-up" module, can be used for left or right-hand opening doors, supporting the lock for longer durability. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area, to cancel the possible mounting inaccuracies. Concealed, non-loosening screwed joint with M5 stainless steel screw and sleeve combination as well as the pivot disappearing into the leaf.
Rose cap round, made of stainless steel (1.4301), diameter 55 mm, 10.5 mm high, 1.5 mm wall thickness.
Surface satin finished
Designed and tested for the projects segment, user category to EN 1906 - Class 4 fitting with spindle 8 - 8.5 mm
user category: Class 4
Durability: Class 7
Door weight: No classification specified
Fire resistance: Class 0
Safety: Class 1
Corrosion resistance: Class 4
Burglary protection: Class 0
Design-type: A

Certificates

HEWI Heinrich Wilke GmbH
Postfach 1260
D-34442 Bad Arolsen
Telephon: +49 5691 82-0
Fax: +49 5691 82-319
info@hewi.de
www.hewi.com