

Wymiary w mm

Podobne zdjęcie

Właściwości

Vacant/Engaged fitting

with flat roses according to DIN 18255 and EN 1906 and inlay made of coloured, matt polyamide, consisting of: door lever handle design 251.21PB ... made of matt polyamide, through-dyed, 21.3 mm diameter, with shank guide and grub screw M5 for additional fixing of the door lever handle on the square spindle, for optimum transfer of force to the door leaf.

Flat lever and toilet door roses, 306.23PBVINR..., round, diameter 52 mm, 4.0 mm high. Concealed, non-loosening connection: fixed rotating bearing of the lever handle and the roses, and support pin that dips into the door leaf. Fast and easy assembly by latching in preassembled assemblies. Toilet version with emergency opening by means of coin and optionally with or without occupancy disc (red/green indicator) on the outside.

Rose material stainless steel (1.4301) matt in PVD-coating,

Rose insert made of matt polyamide

Designed and tested for the projects segment, user category to EN 1906 - Grade 3

Durability: Grade 7

Door weight: No classification specified

Fire resistance: Grade 0

Safety: Grade 0

Corrosion resistance: Grade 4

Security: Grade 0


Type of operation: U

Wyróżnienia



GERMAN
DESIGN
AWARD
WINNER
2019

Kolory / Powierzchnie



99 (czysta biel)



92 (szary antracytowy)



90 (czerń jetowa)