







Similar picture

Dimensions in mm

Properties

LED tilt-mirror of the series 801, LED plus

- · rectangular, illuminated laminated glass mirror with sanded edges
- · integrated shatter protection and integrated LED lights on the side, left and right
- the mirror can be tilted to max 28° using a crank and rope, and can therefore be used when standing or sitting
- · for wall mounting
- with rope pulley for pre-wall installation
- direct connection 200-240 V
- · with two high-quality LED aluminium light profiles attached to the back of the mirror
- light colour can be set freely from warm white to cold white (approx. 3000 6500 Kelvin), total output approx.
 9.6 Watt
- · Light intensity can be dimmed steplessly
- Light can be controlled with a battery-free Bluetooth cordless wall switch (maintenance-free) with EnOcean-technology (included in delivery) or with an existing mobile end device (free Casambi App)
- Cordless wall switch pre-programmed incl. Direkt Opus 55 Inform frame. The central part can be used on site as part of other switch series with an inner dimension of 55 x 55 mm.
- · Memory function: last selected light setting is saved for the following use
- LED and ballast are protected, protection class II, rating IP 44
- Mirror 600 mm wide, 540 mm high and 6 mm thick
- Mirror made of laminated glass
- Holding elements and crank made of high-gloss polyamide acc. to HEWI colour table

Telefon: +49 5691 82-0

Telefax: +49 5691 82-319

- This product contains a light source of energy efficiency class G
- CE and UKCA marking acc. to EMC 2014/30/EU
- Suitable for power grids with mains voltages between 200 and 240 V and mains frequencies of 50 and 60 Hz

Certificates



Colours / Surfaces

