

Similar picture

Properties

Duo mobile hinged support rail, System 900

- two parallel, round gripping levels arranged on top of each other
- · with toilet roll holder and radio-controlled toilet flushing mechanism
- right-hand version
- · can be folded upwards and folded downwards with braked movement
- for mobile use
- for easy and flexible retrofitting on existing, preassembled mounting plate 900.50.001XA, must be ordered separately
- · toolless and quick installation by simple attachment of the hinged support rail
- · secured by fixing screw to prevent unintentional removal
- · blue button (wave symbol) for triggering the toilet flushing mechanism
- transmission frequency 868.4 MHz
- suitable for radio-controlled toilet flushing systems made by Geberit, Friatec, Mepa, Sanit, Viega, TECE and Grohe
- projection 700 mm, 210 mm high and 101 mm wide, top rail diameter 33.7 mm, bottom rail diameter 25 mm
- weight capacity up to 100 kg
- made of stainless steel, satin
- floor supports 900.50.020XA and 900.50.021XA for retrofitting
- produced in accordance with CE- and UKCA-Regulation (EU) 2017/745 on medical devices
- fulfils the ÖNORM B1600/1601 and SIA 500 requirements

Awards





Technical information subject to alteration, 25.04.2024

Dimensions in mm