

Similar picture

Properties

Duo mobile hinged support rail, System 900

- · two parallel, round gripping levels arranged on top of each other
- with radio-controlled toilet flushing mechanism
- right-hand version
- · can be folded upwards and folded downwards with braked movement
- for mobile use
- for easy and flexible retrofitting on existing, preassembled mounting plate 900.50.001XA, must be ordered separately
- · toolless and quick installation by simple attachment of the hinged support rail
- · secured by fixing screw to prevent unintentional removal
- · blue button (wave symbol) for triggering the toilet flushing mechanism
- transmission frequency 868.4 MHz
- suitable for radio-controlled toilet flushing systems made by Geberit, Friatec, Mepa, Sanit, Viega, TECE and Grohe
- projection 750 mm, 210 mm high and 101 mm wide, top rail diameter 33.7 mm, bottom rail diameter 25 mm
- weight capacity up to 100 kg
- made of stainless steel, satin
- floor supports 900.50.020XA and 900.50.021XA for retrofitting
- produced in accordance with CE- and UKCA-Regulation (EU) 2017/745 on medical devices
- fulfils the requirements applicable in Belgium (CWATUPE, WVG Vlaanderen) regarding the projection of the hinged support rail at the toilet

Awards



Certificates

Technical information subject to alteration, 21.12.2023

Dimensions in mm