



Dimensions in mm

Properties

Mobile hinged support rail Duo System 800 K

- for easy and flexible retrofitting on existing, preassembled mounting plate: 950.50.014XA, must be ordered separately
- for mobile use
- with two gripping levels arranged above each other
- upper rail is merged with the top rail at an angle of 135°
- upper rail (diameter 33 mm) for holding on to and providing support
- bottom rail (diameter 25 mm) starts at a distance of 250 mm from the front edge of the upper rail and is used for holding on to and for turning in from the side
- 700 mm projection, bracket 181 mm high and 130 mm wide
- can be folded upwards and, folded downwards with braking mechanism
- made of high-quality polyamide in HEWI colours 98 (signal white) or 99 (pure white)
- with continuous, anti-corrosion steel core and bracket made of steel with cover made of high-quality polyamide
- tool-free and quick installation by means of short, simple hanging
- secured against unintentional removal
- unlocking for flexible use by spring actuation
- with toilet roll holder 950.50.01090, toilet roll holder with WC flushing mechanism 950.50.07090 (right), 950.50.07190 (left) and floor supports 950.50.020XA, 950.50.025XA and 950.50.026XA for retrofitting
- produced in accordance with CE- and UKCA-Regulation (EU) 2017/745 on medical devices
- fulfils the ÖNORM B1600/1601 and SIA 500 requirements
- weight capacity 100 kg

Certificates

