





Dimensions in mm

Properties

Hinged support rail Duo

- with two gripping levels arranged above each other
- upper rail is merged with the top rail at an angle of 135°
- upper rail made of rectangular profile, 40 mm wide and 30 mm, provides a wide support surface and large radii for pleasant gripping, used to hold on tight and for support
- bottom rail (diameter 25 mm) starts at a distance of 250 mm from the front edge of the upper rail and is used for holding on to and for turning in from the side
- 700 mm projection, wall mounting plate 181 mm high and 130 mm wide
- · can be folded upwards and, folded downwards with braking mechanism
- made of high-quality stainless steel, satin surface finish
- wall-mounting plate cover made of high-quality polyamide in stainless steel look
- stable three-point fixing
- for wall mounting with concealed, non-corrosive and tested fixing materials for different wall systems (must be ordered separately)
- sealing tape for sealing the fixing points is included in the scope of supply
- with toilet roll holder 950.50.01150, toilet roll holder with WC flushing mechanism 950.50.07290 (right),
 950.50.07390 (left), floor supports 950.50.020XA, 950.50.025XA, 950.50.026XA and arm pad 950.50.03192 for retrofitting
- produced in accordance with CE- and UKCA-Regulation (EU) 2017/745 on medical devices

Telefon: +49 5691 82-0

Telefax: +49 5691 82-319

- fulfils the ÖNORM B1600/1601 and SIA 500 requirements
- · weight capacity 100 kg

Certificates

