

Podobne zdjęcie

Wymiary w mm

Właściwości

Tripple-roll hinge

for rebated doors with weight up to 180 kg.






Built-in door panel by milling and for recessed mounting on wood, steel and aluminium doorframe in the three-dimensionally adjustable retention element VX... and VZX...

made of polyamide with steel support made of galvanised 4 mm sheet steel and closed hinge roll, 160 mm height, hinge roll diameter 21 mm, twist-proof stainless steel pin and maintenance-free polyamide plain bearings.

Polyamide caps for covering the cut recess and the screw fixing. can be used on right and left-hung doors.

Four steel bushings prevent the stainless steel pin from slipping through in case of fire and therefore lowering the door. CE marking according to Construction Product Regulation No. 305 / 2011.

Kolory / Powierzchnie

 24 (pomarańczowy)	 55 (błękit akwaticzny)	 86 (piasek)	 97 (jasnoszary)
 33 (rubinowa czerwień)	 72 (może być zielony)	 90 (czern jetowa)	 98 (sygnał biały)
 36 (koral)	 74 (jabłko zielone)	 92 (szary antracytowy)	 99 (czysta biel)
 50 (stalowoniebieski)	 18 (żółta musztarda)	 95 (szary kamień)	 84 (umbra)