



Podobne zdjęcie

Wymiary w mm

Właściwości

Tripple-roll hinge
for rebated doors with weight up to 180 kg.
Built-in door panel by milling and for recessed mounting on wood, steel and aluminium doorframe in the three-dimensionally adjustable retention element VX... and VZX...
made of polyamide with steel support made of galvanised 4 mm sheet steel and closed hinge roll, 160 mm height, hinge roll diameter 21 mm, twist-proof stainless steel pin and maintenance-free polyamide plain bearings.
Polyamide caps for covering the cut recess and the screw fixing. can be used on right and left-hung doors.

Kolory / Powierzchnie

24 (pomarańczowy)	55 (błękit akwatyczny)	86 (piasek)	97 (jasnoszary)
33 (rubinowa czerwień)	72 (może być zielony)	90 (czerń jetowa)	98 (sygnał biały)
36 (koral)	74 (jabłko zielone)	92 (szary antracytowy)	99 (czysta biel)
50 (stalowoniebieski)	18 (żółta musztarda)	95 (szary kamień)	84 (umbra)

Zastrzega się możliwość wprowadzania zmian technicznych, 26.04.2024

HEWI Heinrich Wilke GmbH
Sp. z o.o. Oddz. w Polsce
Ul. Lelka 26
02-812 Warszawa
Tel.: 22 330 00 51
Faks: 22 330 00 50
info@hewi.pl