

BACKREST RAIL

STATIONARY HINGED SUPPORT RAILS

NECESSARY FOR ALL

Polyamide



950.51.90090

- c to c 650-700 mm adjustable on site
- 150 mm deep
- backrest made of glass fibre reinforced polyamide in HEWI colours 98 (signal white) and 92 (anthracite grey)
- mounting bar made of metal, white powder-coated

Polyamide CE




950.50.11090 | 600 mm **950.50.12090 | 700 mm**
950.50.13090 | 850 mm

950.50.11091 | 600 mm **950.50.12091 | 700 mm**
950.50.11099 | 600 mm **950.50.12099 | 700 mm**
950.50.13091 | 850 mm **950.50.13099 | 850 mm**


CE

Stainless steel CE




950.50.610XA | 600 mm **950.50.620XA | 700 mm**
950.50.630XA | 850 mm

WARM TOUCH CE



950.50.11050 | 600 mm **950.50.12050 | 700 mm**
950.50.13050 | 850 mm

Chrome CE



950.50.61040 | 600 mm **950.50.62040 | 700 mm**
950.50.63040 | 850 mm

BM17.4
 For fixing on walls made of concrete (> C20/C25)
 National technical approval number: ETA-11/0493
 additionally: injection mortar (HEWI item No.: 200311)
 or to be provided on site: injection mortar HIT-HY200A (Hilti), extrusion tool HDM (Hilti)

BM10.4
 For fixing on walls made of concrete (> C20/C25)

BM11.4
 For fixing on walls made of auto-claved aerated concrete (> P2)
 additionally: injection mortar (HEWI item No.: 200266), conical drill bit (HEWI item No.: 171041)
 or to be provided on site: injection mortar HIT-HY 270 (Hilti), extrusion tool HDM (Hilti), conical drill bit TE-C PB 22/100 (Hilti)

BM12.4
 For fixing on lightweight walls with rear lining made of laminated timber boards (with waterproof bonding, at least 30 mm thick required, e.g. studs or prewall installation)

BM13.4
 For fixing on lightweight walls with integrated steel plates (e.g. studs or pre wall installation)

BM18.4
 For fixing on walls with mesh sleeve ø 18 mm
 · hollow concrete block
 · vertically perforated bricks
 · hollow lightweight concrete block
 · lightweight aggregate concrete with open structure
 National technical approval number: ETA-13/1036
 without mesh sleeve
 · solid bricks, perforated calcium silicate block
 National technical approval number: ETA-13/1036
 additionally: injection mortar (HEWI item No.: 200266)
 or to be provided on site: injection mortar HIT-HY 270 (Hilti), extrusion tool HDM (Hilti)

Backrest rail can also be combined with mobile versions.