


BACKREST RAIL

STATIONARY HINGED SUPPORT RAILS

NECESSARY FOR ALL

Polyamide



950.51.90090

- c to c 650-700 mm adjustable on site
- 150 mm deep
- backrest made of glass fibre reinforced polyamide in HEWI colours 98 (signal white) and 92 (anthracite grey)
- mounting bar made of metal, white powder-coated

Polyamide



950.50.11090 | 600 mm



950.50.12090 | 700 mm
950.50.13090 | 850 mm




950.50.11091 | 600 mm
950.50.11099 | 600 mm




950.50.12091 | 700 mm
950.50.12099 | 700 mm
950.50.13091 | 850 mm
950.50.13099 | 850 mm

Stainless steel



950.50.610XA | 600 mm



950.50.620XA | 700 mm
950.50.630XA | 850 mm

WARM TOUCH




950.50.11050 | 600 mm




950.50.12050 | 700 mm
950.50.13050 | 850 mm

Chrome



950.50.61040 | 600 mm



950.50.62040 | 700 mm
950.50.63040 | 850 mm

BM17.4

For fixing on walls made of concrete (> C20/C25)
National technical approval number: ETA-11/0493

additionally: injection mortar (HEWI item No.: 200311)
or to be provided on site:
injection mortar HIT-HY200A (Hilti),
extrusion tool HDM (Hilti)

BM10.4

For fixing on walls made of concrete (> C20/C25)

BM11.4

For fixing on walls made of auto-claved aerated concrete (> P2)

additionally: injection mortar (HEWI item No.: 200266), conical drill bit (HEWI item No.: 171041)
or to be provided on site:
injection mortar HIT-HY 270 (Hilti),
extrusion tool HDM (Hilti),
conical drill bit TE-C PB 22/100 (Hilti)

BM12.4

For fixing on lightweight walls with rear lining made of laminated timber boards (with waterproof bonding, at least 30 mm thick required, e.g. studs or prewall installation)

BM13.4

For fixing on lightweight walls with integrated steel plates (e.g. studs or pre wall installation)

BM18.4

For fixing on walls with mesh sleeve ø 18 mm

- hollow concrete block
- vertically perforated bricks
- hollow lightweight concrete block
- lightweight aggregate concrete with open structure

National technical approval number: ETA-13/1036

without mesh sleeve

- solid bricks, perforated calcium silicate block

National technical approval number: ETA-13/1036

additionally: injection mortar (HEWI item No.: 200266)
or to be provided on site:
injection mortar HIT-HY 270 (Hilti),
extrusion tool HDM (Hilti)