





Dimensions in mm

Properties

Electronic washbasin tap

- PVD coated stainless steel look, cubic
- Flow rate 5 l/min
- Battery operation
- Use of a commercially available long-life lithium battery (type CR-P2)
- For cold and mixed water
- Cold water: 3/8" T-distributor required, see accessories art. no. 65755
- can be used with backflow preventer with dirt filter, see accessories art. no. 70247
- Laminar jet regulator with dynamic flow rate control 5 l/min, angle adjustable and theft-proof
- Adjustable, active, false trigger resistant infrared sensor system
- Electronic module with adjustable detection range, hygiene flush, continuous flush and cleaning mode
- Sensor parameters preset at the factory: follow-up time: approx. 1-2 s, continuous operation: max. 4 min, detection range: 200 mm, cleaning mode: 60 s, hygiene flush is deactivated
- Asymmetrical detection range, stable object detection
- Settings and service also possible via app using a smartphone, see accessories art. no. 65713
- In case of operating voltage failure, safety shutdown, user-defined settings are retained
- Without temperature adjustment lever: High hygiene, vandal and misuse proof
- the preset temperature lies in the comfort zone of 30°C to 36°C
- Temperature can be set and adjusted easily during assembly thanks to access on the side
- Connection via flexible pressure hoses with interwoven hot/cold marking 450 mm long, G 3/8"
- integrated dirt strainers
- Brass fitting body
- 145 mm high, 193 mm projection
- rigid spout
- without drain set
- Noise class 1
- suitable for thermal disinfection according to WRAS
- corresponds to DIN EN 15091
- CE and UKCA marking according to EMC 2014/30/EU

Awards



Certificates

