



Properties

Vacant/Engaged fitting

in T-technology with stainless steel rosettes to DIN 18255 and DIN EN 1906, consisting of:

Lever handle model 271X... in L made of stainless steel (1.4301), Diameter 21.3 mm, with attachment guide and M5 grub screw to fix the lever handle to the square spindle.

Quick installation of the lever handles in the base parts pre-mounted on the door. Loosening-proof connection between pin and lever handle.

Plastic rose bases with support plugs recessed into the door leaf. Concealed, Loosening-proof screw connection.

Rose cap, round, made of stainless steel (1.3401), Diameter 55 mm, 10.5 mm high, 1.5 mm wall thickness.

WC version with emergency opening by means of square spindle or coin and occupancy disc (red/white indicator) on the outside.

Matt ground surface

Designed and tested for solid leaf doors in medium-frequented commercial buildings, Utilisation category according to DIN EN 1906 - class 4 (square 8 or 8.5 mm). Set with square spindle 7, 8 or 8.5 mm for door thicknesses from 28.1 - 58.0 mm.

Utilisation category: Class 4

Durability: Class 7

Door weight: No classification specified

fire resistance: Class 0

Safety: Class 1

Corrosion resistance: Class 4

Burglary protection: Class 0

Design type: U

Sustainability: EPD Environmental Product Declaration

Awards



Certificates

