

Dimensions in mm

Properties

Apartment door fitting

in H-technology with roses according to DIN 18255 and EN 1906 made of stainless steel, PVD coated, consisting of:

Knob model 276X in stainless steel and lever handle Model 273X... with stainless steel (1.4301), PVD coated, Lug diameter 21.3 mm, with stepped shoulder guide and groove, with set screw M5 as additional fixing of lever and spindle for optimal transfer of force to door leaf. The lever handle fulfils the guidelines of the Bundesverband der Unfallkassen e. V. (BUK) - safety distance to the closing edge 25 mm.

The lever handle meets the standards of EN 179.

Installed by simply latching the lever handle into the base parts pre-mounted on the door. The latching can be released using the dismantling tool.

Rose 315.21X... and 316X..., Substructure 315.21X... in plastic-steel composite finish with black zinc/nickel surface for optimum corrosion protection, integrated spring-assisted restraining "hold-up" module, can be used for left or right-hand opening doors, supporting the lock for longer durability. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area to eliminate any possible installation inaccuracies.

Rose cap, oval, made of stainless steel (1.3401), 33 x 71 mm, 10.5 mm high, 1.5 mm wall thickness.

PVD coated

Designed and tested for projects, Category of use according to DIN EN 1906 - Class 4 Fire protection set with square spindle 8- 8.5 mm

usage category: Class 4

Durability: Class 7

Door weight: No classification specified

fire resistance: Class 0

Safety: Class 1

Corrosion resistance: Class 4

Burglary protection: Class 0

Design type: A





Awards




Certificates



Colours / Surfaces

	WR (brushed nickel)
	VT (brushed gold)
	SV (brushed bronze)
	RB (brushed copper)

	LP (brushed brass)
---	--------------------